

Chains

project's NW. about 20 chs.

Descend.

72.95 Head of ravine, 85 ft. below top of spur, drains N.15°W.

Ascend gradually.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 1,2,35 and 36, with brass cap marked

T5N	R56E
S35	S36
S2	S1
T4N	
1916	

and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

No suitable bearing trees available.

Cor. stands 75 ft. above head of ravine.

land, rolling hills on W. 50 chs.; mountainous on E. 30 chs.; general exposure and drainage to NW. and N.; soil, very stony on surface of limestone and quartzite formation; 4<sup>th</sup> rate; scattering scrub cedars on W. 54½ chs.; medium growth of cedars and pinon pine on E. 25½ chs.; scattering undergrowth of sage brush, shadscale and grass with scant grazing on the mile.

East, bet. secs. 1 and 36.

Over mountainous land, through medium growth of cedars and pinon pine and scattering undergrowth of sage brush, shadscale, greasewood and grass.

Ascend.

3.00 Head of ravine, 1½ chs. wide, 50 ft. deep, drains NW.

Continue ascent.

13.35 Top of rocky spur, 355 ft. above sec. cor., projects N.15°E. about 15 chs.

Descend abruptly.

28.90 Bottom of ravine, 325 ft. below top of spur, drains N.

Ascend.

33.15 Top of spur, 75 ft. above ravine, projects N. 1 ch.

Descend.