

Chains

of cor.

47.40 Dry wash, 50 lks. wide, 6 ft. deep, drains W.

55.00 Point of ascent over small rocky knoll, bears NE. and W.

58.50 Top of small rocky knoll, 45 ft. above point of ascent,  
bears NE., 2 chs. dist. and SW.,  $2\frac{1}{2}$  chs. dist.

Descend.

61.00 Bottom of descent, 35 ft. below top of knoll, bears NE.  
and SW.

Thence, nearly level.

80.93 Intersect the First Standard Parallel North, 10.60 chs., N.  
89° 40' W. of the std. cor. of secs. 35 and 36, heretofore  
described.Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in  
the ground for C.C. of secs. 1 and 2, with brass cap  
marked

T6N R56E	
S35	
-----	
S2	S1
T5N	R56E
C C	
1916	

and raise a mound of stone, 3 ft. base, 2 ft. high, S.  
of cor.Land, rolling with a general drainage to the W.; soil,  
light brown sandy gravelly loam of hard texture, 26 ins.  
deep with brown and black coarse gravel and scattering  
loose lime rock on surface; no timber; undergrowth,  
scattering sage brush, shadscale, greasewood and grass;  
fair grazing on the mile.From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of  
the Tp., heretofore described

N.0° 01' W., bet. secs. 34 and 35.

Over rolling land, through scattering scrub cedars and  
medium undergrowth of sage brush, shadscale and scatter-  
ing greasewood, juniper and grass.

Descend gradually.