


Chains

N.0° 01'W., bet. secs. 2 and 3.

Over rolling land, through scattering undergrowth of sage brush, shadscale, greasewood and grass.

16.20 Dry wash, 20 lks. wide, 1 ft. deep, drains NW.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked




Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

55.00 Wagon Road, Blue Eagle to Tonopah, bears NE. and SW.

80.94 Intersect the First Standard Parallel North, 9.24 chs. N.89° 36'W. of the standard cor. of secs. 34 and 35, heretofore described.

Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for C.C. of secs. 2 and 3, with brass cap marked



and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, rolling; general drainage to the NW.; soil, coarse brown, black and white gravel, 1 to 2 ins. deep and scattering loose lime rock on surface; subsoil, light brown gravelly sandy loam of hard texture; no timber; undergrowth, scattering sage brush, shadscale, greasewood and grass with fair grazing on the mile.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., heretofore described.

N.0° 02'W., bet. secs. 33 and 34.

Over rolling land, through medium undergrowth of sage