Subdivision of T.5 N., R.56 E.

Chains

Dig pits, 18x18x12 ins., N: and S. of post, 3 ft. dist. 81.29 Intersect the First Standard Parallel North, 8.45 chs. S.89° 39'W. of the standard cor. of secs. 33 and 34, heretofore described.

> Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for G.C. of secs. 3 and 4, with brass cap marked

Dig pits, 24x18x12 ins. crosswise on each line, E. and W., 3 ft., and S. of post, 7 ft. dist.

Land, gently rolling with a slight general drainage to the W.; soil, very light alluvial damp sandy clay loam mixed with some alkali, 26 ins. deep; no timber; medium undergrowth of greasewood and shadscale and scattering sage brush and grass on S. 15 chs.; dense undergrowth of tall greasewood, shadscale, rabbit brush and scattering sage brush and grass on N. 66 chs.; good grazing on the mile.

From the cor. of secs. 4,5,32 and 33, on the S. bdy. of the Tp., heretofore described.

N.0° 03'W., bet. secs. 32 and 33.

Over rolling land, through scattering undergrowth of shadscale, sage brush, greasewood and grass.

Set an iron post, 3 ft. long, 1 in. in dia., 14 ins. in the ground to solid rock and erect a mound of stone, 3 ft. base, 1 ft. high, around post for  $\frac{1}{4}$  sec. cor., with brass cap marked

> 832 833 1916

40.00