

Survey of Portion of the 9th. Standard Parallel N., Range 30 E.

Chains From the reestablished standard $\frac{1}{2}$ cor. of sec. 35,
heretofore described.

West along the S. bdy. of sec. 35.

Over rolling land, crossing narrow meadow.

6.50 Dry channel of Round Mountain creek, 6 lks. wide, 3 ft.
deep, course S. 60° E.; gradually asc. along NE. slope
along S. edge of meadow.

10.00 Leave meadow, bears E. and NW.

11.40 Wire fence, bears N. 60° W. and S. 60° E.

11.50 Ascend steep NE. slope.

22.40 Gulch, course N. 20° E.

26.30 Top of granite ledge on spur, 240 ft. above bed of creek,
projects N. 20° E.; descend abrupt NW. slope.

35.30 Dry channel of Round Mountain creek, 20 lks. wide, 4 ft.
deep, course N. 45° E., 30 ft. below top of spur; asc.
SE. slope 60 ft. to the sec. cor.

40.00 Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the
ground for the standard cor. of secs. 34 and 35, with
brass cap mkd.

S C
T46NR30E

S34 | S35

1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

This cor. is located at the S. base of a ledge of rock,
3 ft. high, bearing E. and W.

Land, heavy rolling hills, drainage SE.

Soil, deep rich dark loam along narrow creek valley,
gravelly and having considerable rocks and boulders
on surface; hill slopes generally very rocky, the soil
being composed of decomposing granites with several
high exposed ledges of the same formation.

Undergrowth, sagebrush, bunch grass and wild meadow pasture,

Timber, light growth of scrub mountain mahogany on W.

20.00 chs.