

## Survey of Portion of South Boundary of T. 47 N., R. 30 E.

Chains I continue my resurvey west; gradually ascend 20 ft. to the cor. of secs. 4 and 5.

89.43 Reestablished the cor. of secs. 4 and 5 of T. 46 N., R. 30 E. as follows:

Set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of secs. 4 and 5 of T. 46 N., R. 30 E., with brass cap mkd.

S5 | S4  
T46NR30E

1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.

Land, rolling valley, drainage northward. Soil, sandy and gravelly light brown clay loam, 8 ins. deep, compact clay subsoil. Undergrowth, sagebrush and scant growth bunch grass. No timber.

## Survey of Portion of South Boundary of T. 47 N., R. 30 E.

-----  
From the cor. of secs. 32 and 33, heretofore described.

West on a true line along the S. bdy. of sec. 32.

Over rolling valley land, gradually ascending.

9.42 The reestablished cor. of secs. 4 and 5 of T. 46 N., R. 30 E., heretofore described.

23.40 Enter rolling hills; ascend E. slope.

40.00 Set an iron post 3 ft. long, 1 in. diam., 16 ins. in the ground to solid rock and in a mound of stone, for the  $\frac{1}{4}$  cor. of sec. 32, with brass cap mkd.

$\frac{1}{4}$  S32

1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

42.40 Top of low ridge, bears N.  $30^{\circ}$  E. and S.  $30^{\circ}$  W., 300 ft. above sec. cor.; ascend over rolling land 200 ft. to the sec. cor.

62.65 Dry wash, 20 lks. wide, 3 ft. deep, course N.  $60^{\circ}$  E.