

Survey of Portion of South Boundary of T. 47 N., R. 30 E.

Chains

- 71.50 Top of low spur, projects N. 30° E.; descend.
- 78.70 Gulch, 12 ft. deep., course N. 30° E. turning easterly; ascend.
- 80.00 Set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of secs. 31 and 32, with brass cap mkd.

T47NR30E

 S31 | S32

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Land, rolling foothills, drainage to the N. and NE.
 Soil, stony and rocky light brown clay loam, medium texture, washed on slopes, some exposed granite and quartzite ledges.
 Undergrowth, sagebrush and fair growth bunch grass.
 No timber.

From the cor. of secs. 31 and 32,
 West along the S. bdy. of sec. 31.
 Over mountainous land, ascend steep E. slope.

- 24.20 Top of dividing ridge, 620 ft. above sec. cor., bears N. 20° E. and S. 20° W.; descend NW. slope.

- 40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the ¼ cor. of sec. 31, with brass cap mkd.

¼ S31

1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 42.10 Gulch, 420 ft. below summit of divide, course N. 20° W.; ascend along N. slope.

- 50.10 Dry gulch, 10 lks. wide, 3 ft. deep, course N. 40° E.; asc. E. slope.

- 58.00 Top of ridge, 90 ft. above bottom of gulch, bears N. 30° E. and S. 30° W.; descend.

- 67.60 Cross gulch near head, 110 ft. below top of ridge, course