

Resurvey of S. bdy. T 24 N, R 18 E.

Chains

Set old cor. alongside of post.
Land, on the W. $\frac{1}{2}$ mile,
Rolling mountains of granite, with a N. and S. trend.
Soil, dry, gravelly and rocky. 3rd. rate. Fair feed of
sagebrush, with some weeds and grass. No timber.

N 89°24'W, bet. secs. 6 and 31

Over high, rolling granite mountains.
Asc. gentle S.E. slope.

7.24 Intersect the old closing cor. of Tps. 23 and 24 N, R
18 E. Reestablish this cor. as follows, at the same point,
Set an iron post, 3 ft. long, 3 ins. dia. 24 ins. in the
ground for cor. of Tps. 23 and 24 N, R 18 E, with brass
cap mkd.

T 24 N
R 18 E
S 31
S 6
T 23 N

1916

39.95 dig pits 30 x 24 x 12 ins. on each line N. and S. 4 ft.
and E. of post 8 ft. dist. Set old cor. alongside of post.
The old $\frac{1}{2}$ sec. cor.
Land, rolling mountains of granite, with a N. and S. trend.
Soil, dry, gravelly and rocky. 3rd. and 4th. rate. Fair
feed of sagebrush, with some grass and weeds. No timber.

Resurvey of Fractional Subdivision,
T 24 N, R 18 E.

Begin at the cor. of secs. 17, 18, 19 and 20.
Re-establish this cor. as follows:

At the same point, set an iron post, 3 ft. long, 2 ins.
dia., 24 ins. in the ground for cor. of secs. 17, 18, 19
and 20, with brass cap mkd.

T 24 N R 18 E
S 18 S 17
S 19 S 20
1916

dig pits 18 x 18 x 12 ins. in each sec. 5 $\frac{1}{2}$ ft. dist. and
set the old cor. alongside of post.

Thence S 89°1'W, bet. secs. 18 and 19, resurveying.

7.29 Intersect the closing cor. of secs. 18 and 19, on the
State line, and re-establish this cor. as follows;

At the same point, set an iron post, 3 ft. long, 2 ins.
dia., 24 ins. in the ground for cor. of secs. 18 and 19,
with brass cap mkd.

T 24 N
R 18 E
S 18
S 19

1916