

W. bdy. of T 17 N, R 35 E.

Chains

- 15.00 Low spur, slopes S.W., 20 ft. above wash.
- 16.90 Wash, course S 60°W.
- 31.60 Telephone line, bears S 55°W and N 55°E.
- 33.50 Road, bears S 40°W and N 40°E
- 33.60 Power line, bears S.W. and N.E.
- 34.50 Telephone line, bears S.W. and N.E.
- 35.00 Low spur, slopes S.W., desc. N.W. slope.
- 37.00 Large wash, course S 65°W
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the ground for $\frac{1}{2}$ sec. cor. with brass cap mkd.

$$\begin{array}{c} \frac{1}{2} \\ \text{S 1} \quad | \quad \text{S 6} \\ 1916 \end{array}$$

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Asc. S. slope of foot hills.

- 57.80 High, spur, slopes S.E., 220 ft. above wash. Desc. N.E. slope.
- 61.70 Deep ravine, course S 35°E, 45 ft. below spur. Asc. southerly slope.
- 69.30 High spur, slopes S 55°E, 145 ft. above ravine. Desc. N. slope.
- 73.90 Large ravine, course S 60°E, 40 ft. below spur. Asc. S. slope.
- 78.40 Spur, slopes S 60°E, 95 ft. above ravine. Desc. N.E. slope.
- 80.00 25 ft. below spur.
- Set an iron post, 3 ft. long, 3 ins. dia., 24 ins. in the ground for cor. of Tps. 17 and 18 N., Rgs. 34 and 35 E. with brass cap mkd.

$$\begin{array}{c} \text{T 18 N} \\ \text{R 34 E} \quad \text{R 35 E} \\ \text{S 36} \quad | \quad \text{S 31} \\ \hline \text{S 1} \quad | \quad \text{S 6} \\ \text{T 17 N} \end{array}$$

1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

Land, S. 45.00 chs. is rolling land, sloping to the S.W.