


16     Retracement of a portion of Subdivisions of T. 36 N., R. 18 E.

Chains     2, 3, 34 and 35, on the N. Bdy. of the Tp. hereinafter described. The bearing of this mile is therefore N. 0° 47' E. and its length is 79.37 chs.

Independent Resurvey of the 7th Standard Parallel North, through R. 18 E.

Chains     At a point of intersection of a blank line produced west 481.23 chs. from the old standard cor. of Tps. 36 N., Rs. 19 and 20 E., heretofore described, with the E. Bdy. of T. 36 N., R. 18 E., produced south 248.70 chs. from the old cor. of secs. 13, 18, 19 and 24, hereinafter described, I reestablish the standard cor. of Tps. 36 N., Rs. 18 and 19 E. as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 10 ins. in the ground, to solid rock and in a mound of stone, for the standard cor. of Tps. 36 N., Rs. 18 and 19 E., with brass cap mkd.



1916

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

A juniper tree, 16 ins. diam., bears N. 22° 40' W., 387 lks. dist., mkd. T 36 N R 18 E S 36 S C B T.

A juniper tree, 24 ins. diam., bears N. 6° E., 157 lks. dist., mkd. T 36 N R 19 E S 31 S C B T.

Thence West, on a true line, bnt S. e Bdy. of sec. 36.

Over mountainous land; descend steep NW. slope through scattered juniper timber.

14.40     Bottom of ravine, running spring water, 1 lk. wide, 2 ins. deep, 130 ft. below stand. Tp. cor., course N. 40° E.; ascend steep and rocky E. slope.

20.20     Ascend more gradual slope.

38.80     Top of rimrock ledge, 6 ft. high, facing E. and bearing N. and S., 400 ft. above ravine; ascend gradually over