

Chains

ground, for $\frac{1}{4}$ cor. of sec. 19, with brass cap mkd.

$\frac{1}{4}$
S19
1916

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

✓ 53.30 Road, bears N. 70° E. and S. 70° W.

✓ 62.70 Road, bears N. 30° W. and S. 30° E.

✓ 66.40 Road, bears N. 75° W. and S. 75° E.

✓ 68.20 Road, bears E. and W. Main road to Surprise Valley.

68.70 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for cor. No. 5 of Tract No. 41, with brass cap mkd.

T36N
R18E
TR41
5
S24
1916

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13 and 24, with brass cap mkd.

T36N
S13
S24
R18E
1919

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling and nearly level valley, drainage to the N.

Soil, stony and rocky on S. 55.00 chs. balance of mile has a deep, dark, sandy loam soil, medium texture, clay and adobe subsoil, Undergrowth, sagebrush, shadscale, greasewood and some rye grass. No timber.

North, on a true line, on E. Bdy. of sec. 13.

Over level valley land, through dense undergrowth.

✓ 4.50 Cross wire fence, bears N. 10° W. and S. 10° E.

✓ 8.70 Intersect the old cor. of secs. 13, 18, 19 and 24, which is a cottonwood post, 3 ins. sq. $2\frac{1}{2}$ ft. above the ground, mkd. as described by the surveyor general, with evident remains of pits and a mound of earth. This cor. being