

Chains

N. Bdy. of tract No. 53, at a point, 6.47 chs. S. 89° 24' E., of cor. No. 3 of tract No. 50, identical with cor. No. 2 of tract No. 53, on E. Bdy. of tract No. 52, heretofore described.

Thence continue on same line and through tract No. 53.

60.58 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S3 | S2
1919

dig pits, 18x18x12 ins. N. and S. of cor. 3 ft. dist.

79.62 Intersect the S. Bdy. of tract No. 53, identical with the N. Bdy. of tract No. 37, at a point, 6.96 chs. S. 89° 25' E., of cor. No. 3 of tract No. 53, identical with cor. No. 2 of tract No. 37, heretofore described.

Thence continue on same course through tract No. 37.

92.15 Road, bears E. and W.

100.58 The cor. of secs. 2, 3, 10 and 11.

Land, nearly level. Soil, light sandy clay loam, medium texture, dry. Heavy clay and adobe subsoil. Undergrowth, sagebrush and a good growth of grass. No timber.

Subdivisions of T. 36 N., R. 18 E.

From the reestablished standard cor. of secs. 33 and 34, on S. Bdy. of the Tp. heretofore described.

N. 0° 02' W., bet. secs. 33 and 34.

Over mountainous land, descend along E. and NE. slopes, through scattering timber.

20.00 Bottom of depression or draw, drains SE.; 190 ft. below standard sec. cor; asc. S. and SE. slope.

33.30 Ascent becomes more steep.

36.40 Top of ascent, 140 ft. above bottom of depression, bears E. and W. ; over dividing ridge bears E. and W.