

Chains ground to solid rock and in a mound of stone, for the  $\frac{1}{4}$  cor. of secs. 18 and 17, with brass cap mkd.

$\frac{1}{4}$   $\frac{S8}{S17}$

1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Along rolling N. slope descend gradually 30 ft. to the closing cor.

80.72 Intersect the Nevada-Calif. State boundary, 15.36 chs. S.  $0^{\circ} 11'$  E. of mile post No. 68, heretofore described.

At the point of intersection I build a cor. as follows: Set an iron post 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, for the closing cor. of secs. 8 and 17, with brass cap mkd.

T36N  
R18E  
C S8 C N  
A S17 C E  
L V  
1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

Land, rolling N. slope, N. exposure. Soil, heavy clay loam, rocky, some exposed outcrops. Undergrowth, sagebrush, bunch grass. No timber.

N.  $0^{\circ} 03'$  W. bet. secs. 8 and 9.

Along steep W. slope of ridge, land heavy rolling.

16.00 Descend steep NW. slope.

29.20 Tuledad creek, running water, 3 lks. wide, 3 ins. deep, course S.  $80^{\circ}$  E. in channel 75 lks. wide, 8 ft. deep, 250 ft. below sec. cor.; ascend more gradual S. slope. 40 ft. to the  $\frac{1}{4}$  sec. cor.

40.00 Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the ground for the  $\frac{1}{4}$  cor. of secs. 8 and 9, with brass cap mkd.

$\frac{1}{4}$   
S8 | S9  
1916