

Chains

60.20 Base of steep descent, 620 ft. below top of ridge; descend more gradual W. slope 150 ft. to the sec. cor.

80.01 The cor. of secs. 4, 5, 8 and 9. Land, mountainous and rolling W. slope, 21.10 chs. E. exposure, balance W. exposure. Soil, rocky clay with a considerable number of exposed ledges, W. 15 chs. more free from rock. Undergrowth, medium growth sagebrush, some bunch grass. No timber.

West on a true line bet. secs. 5 and 8.

Over rolling land, descend gradual W. slope.

5.90 Gulch, 15 lks. wide, 20 ft. below sec. cor., course S. 20° W.; ascend gradual E. slope.

7.60 Road from Surprise Valley to Tuheadad Valley, bears S. 20° W. and N. 20° E.

25.00 Top of low spur 120 ft. above bottom of gulch, projects S. 25° E.; descend SW. slope.

40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the 1/4 cor. of secs. 5 and 8, with brass cap mkd.

1/4 S5  
S8

1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

60.00 Base of rolling hills, bearing NW. and SE., 180 ft. below top of spur; over gentle S. sloping valley land.

80.84 Intersect the Nevada-Calif. State boundary, 15.73 chs. S. 0° 12' E. of mile post No. 67, heretofore described. At the point of intersection I build a cor. as follows: Set an iron post 3 ft. long; 2 ins. diam., 24 ins. in the ground for the closing cor. of secs. 5 and 8, with brass cap mkd.

T36N  
C | R18E N  
A | S5 CE  
L | S8 CV

1916