

Subdivisions of T. 33 N., R. 22 E.

Chains

11.90 Gulch, course N. 75° W.

21.14 A point which is due E. of the reestablished 1/4 cor. of secs. 3 and 10, heretofore described.

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for the cor. of secs. 3 and 10, with brass cap mkd.

T33N
R22E
S3
S10

1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

40.00 Set an iron post 3 ft. long, 1 in. diam.; 26 ins. in the ground for the 1/4 cor. of sec. 2, with brass cap mkd.

1/4
S2

1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E. of cor.

2 seepage springs bear N. 43° 30' W.

Seepage springs bear N. 36° 30' W.

50.30 Small gulch, course W.

61.14 A point which has a northing of 40.00 chs. from the cor. of secs. 3 and 10.

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the 1/4 cor. of sec. 3, with brass cap mkd.

1/4
S3

1916

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

68.40 Gulch, course W.

87.50 Road, bears E. and S. 70° W.

88.20 Ravine with running water, 3 lks. wide, 3 ins. deep, course S. 80° W.; over wet boggy land.

100.40 Intersect the N. bdy. of the Tp., 10.45 chs. S. 89° 54' W.