

Subdivisions of T. 33 N., R. 22 E.

Chains and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

47.00 Bottom of gulch, 20 ft. below top of E. slope, course E.; ascend S. slope.

53.20 Top of low spur, 80 ft. above bottom of gulch, projects E.; descend.


59.40 Bottom of gulch, 60 ft. below top of spur; course S. 80° E.; ascend along rolling E. slope.

63.00 Top of ascent slopes E., 70 ft. above bottom of gulch; desc.

74.70 Bottom of gulch, 20 ft. below top of E. slope; course E.; ascend S. slope 80 ft. to the closing cor.

82.94 Intersect N. bdy. of the Tp., 14.42 chs. S. 89° 57' W. of the cor. of secs. 31 and 32 of T. 34 N., R. 22 E., heretofore described. At the point of intersection I build a cor. as follows:

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for the closing cor. of secs. 5 and 6, with brass cap mkd.



and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

Land, heavy rolling with a general exposure to the N. and E., drainage E. Soil, heavy clay mixed with volcanic rock, some exposed ledges of volcanic formation. Undergrowth, sagebrush, shadscale and scant growth bunch grass. No timber.

From the closing cor. of secs. 5 and 6 on the N. bdy. S. 89° 57' W. on the N. bdy. of sec. 6

25.62 The old ¼ cor. of sec. 31 of T. 34 N., R. 22 E. heretofore described. At this cor. I change the bearing of my line to N. 89° 56' W.

40.00 Set an iron post 3 ft. long, 1 in. diam., on solid rock