

Resurvey and Survey of a portion of the
South boundary of T.12 N., R.50 E.

Chains

- From the cor. of Tps. 11 and 12 N., Rs. 49 and 50 E., heretofore described, I resurvey East, bet. secs. 6 and 31.
- Over rolling land, through medium undergrowth of sage brush, greasewood, shadscale and scattering grass.
- 30.00 Enter level land and additional medium undergrowth of rabbit brush, bears N. and S.
- 39.50 Intersect the $\frac{1}{4}$ sec. cor., which is a sandstone, 9x14x6 ins., lying loose on the ground, but marked and witnessed as described by the surveyor general.
- I reestablish this $\frac{1}{4}$ sec. cor., in its original position as follows:
- Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
- S31
 $\frac{1}{4}$
S6
1916
- Dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.; and bury the old $\frac{1}{4}$ sec. cor. alongside of iron post.
- 44.70 Wagon Road, Hot Creek to Eureka, bears N. and S.
- 71.50 From this point, a spring bears N., $2\frac{1}{2}$ chs. dist.
- 73.00 Slough from spring, 50 lks. wide, 6 ins. deep, drains SE.
- 79.50 Intersect the cor. of secs. 5, 6, 31 and 32, which is a porphyry rock, 6x10x12 ins., lying loose on ground, with no visible marks on same and no traces of old pits; but as this old stone is at about the proper position and there are no other stones in the vicinity, I take this to be the old original corner and reestablish same in its original position as follows:
- Set the same porphyry stone, 6x10x12 ins., 9 ins. in the ground, for cor. of secs. 5, 6, 31 and 32, marked with 5 grooves on E. and 1 groove on W. face; dig pits, 18x18x12 ins., in each sec., $5\frac{1}{2}$ ft. dist.
- Land, rolling on W. 30 chs.; level on E. $49\frac{1}{2}$ chs.; general drainage, to the S. and SE.; soil of the W. 30 chs. is a brown sandy gravelly loam of medium texture, 26 ins. deep; that of the E. $49\frac{1}{2}$ chs. is a damp pliable sandy