

Subdivision of T.12 N., R.50 E.

Chains

Note: On account of steep and impassable granite ledges, N. and S. of this sec. cor., it is impossible to survey in either direction; therefore I return to the cor. of secs. 1,2,11 and 12 and proceed as follows:

N.0° 01'W., bet. secs. 1 and 2.

Over rolling land, through scattering growth of scrub cedars and medium undergrowth of sage brush and scattering greasewood and grass.

40.00 Set a granite stone, 7x12x20 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor., with $\frac{1}{4}$ marked on W. face; no suitable bearing trees available; dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground for cor. of secs. 1,2,35 and 36, with brass cap marked

T13N	R50E
S35	S36
S2	S1
T12N	
1916	

No suitable bearing trees available; dig pits, 18x18x12 ins., in each sec., $5\frac{1}{2}$ ft. dist.

Land, rolling; general drainage, westerly; soil, brown pliable sandy loam of medium texture, 26 ins. deep; scattering growth of scrub cedars; medium undergrowth of sage brush and scattering greasewood and grass; scant grazing, 80 chs.

From the cor. of secs. 2,3,34 and 35, on the S. bdy. of the Tp., heretofore described, I survey

N.0° 01'W., bet. secs. 34 and 35.

Over rough mountainous land, through medium growth of cedars and pinon pine and scattering undergrowth of sage brush, shadscale and grass.

Ascend gradually.