

Resurvey of South Boundary of T. 34 N., R. 19 E.

Chains

of cor.

- 46.36 Top of steep ascent and bench, bears N. 15° E. and S., 450 ft. above creek; over bench land.
- 59.00 Rim rock ledge, 6 ft. high, bears N. and S.; descend steep slope.
- 66.60 Bottom of ravine, 160 ft. below top of bench, course S. 20° W.; ascend steep slope.
- 79.80 Top of ascent and edge of bench, bears N. 30° E. and S., 140 ft. above bottom of ravine; over nearly level bench.
- 80.00 Reestablished the sec. cor. as follows:

Set an iron post 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, for the cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T34NR19E		
S31		S32
S6		S5
T33NR19E		
1916		

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, high level bench cut by deep canyons and ravines running south, slopes of canyons steep and very rocky. Soil, brown clay and adobe, loose lava rocks on the surface, steep slopes of canyons covered with masses of volcanic rock. Undergrowth, medium growth sagebrush and some bunch grass. No timber. Willows along Buffalo creek.

From the reestablished cor. of secs. 5, 6, 31 and 32, West on a true line bet. secs. 6 and 31.

Over slightly rolling bench land, drainage S.

- 40.00 Reestablished the ¼ sec. cor. as follows:

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the ¼ cor. of secs. 6 and 31, with brass cap mkd.

¼	S31
¼	S6
1916	

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 45.00 Descend into draw, edge bears N. and S.