


Retracement of East Boundary of T. 34 N., R. 18 E.

Chains

48.60 Bottom of draw, 50 ft. below $\frac{1}{4}$ cor., course S; ascend

53.40 Rim rock ledge of rock, 5 ft. high, bears N. 10° W. and S. 10° E. 40 ft. above bottom of draw; over slightly rolling bench.

73.34 Intersect a point on the E. bdy. of sec. 36 of T. 34 N., R. 18 E., 19.79 chs., N. 0° 40' W. of the $\frac{1}{4}$ cor. of sec. 36, hereinafter described. At the point of intersection I build a cor. as follows:
 Set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of Tps. 33 and 34 N., R. 19 E., with brass cap mkd.



1916

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.

Land, rolling bench, drainage southward. Soil, heavy clay and adobe, stiff texture, loose and imbedded rock on surface, some exposed ledges of volcanic origin bordering steep descent in to draws. Undergrowth, scant growth sagebrush, some bunch grass. No timber.

start

Retracement of East Boundary of T. 34 N., R. 18 E.

The old cor. of Tps. 33 and 34 N., Rs. 18 and 19 E. is a basalt stone, 10 X 12 X 22 ins., firmly set in a mound of stone, mkd. and witnessed as described by the surveyor general. I obliterate the markings on the NE. and SE. edges of this cor., thus making it a cor. of Tps. 33 and 34 N., R. 18 E., hereafter. On the west side of the cor. I build a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high. *stop*

Thence I retrace,

North on the E. bdy. of sec. 36.

40.15 Intersect a point on E. and W. line, 19 lks. W. of the old $\frac{1}{4}$ cor. of secs. 31 and 36, and hereafter a $\frac{1}{4}$ cor. for sec. 36 only, which is a basalt stone, 10 X 6 X 14 ins.,