

Survey of the Subdivisions of T. 39 $\frac{1}{2}$ N., R. 21 E.

Chains	North on random line bet. secs. 21 and 22.						
37.37	Intersect the N. bdy. at a point 3 lks. W. of the cor. of secs. 21, 22, 33, and 34. Thence, S. 0° 03' W. on true line bet. secs. 21 and 22. Over broken land. Asc. gradual NE. slope.						
21.40	Top of rocky ridge, 50 ft. above sec. cor., bears E. and W.; desc. gradual S. slope 60 ft. to sec. cor.						
28.70	Ravine course E.						
32.40	Top of low ridge, bears E. and S. 45° W.						
37.37	The cor of secs. 21, 22, 27 and 28. Land, rolling mountainous, general drainage NE. Soil, rocky, heavy clay loam, medium depth, solid rock subsoil. Fair growth of sage and bunchgrass. No timber.						
	From the cor. of secs. 4, 5, 32 and 33 on the S. bdy, which is an iron post, 3 ft. long, 3 ins. dia., show- ing 17 ins. above ground; marked and witnessed as described by the surveyor general. I change the marks on the brass cap to read as follows: <table><tr><td>T39$\frac{1}{2}$N S32</td><td>R21E S33</td></tr><tr><td>S5 T39N</td><td>S4 R21E</td></tr><tr><td colspan="2">1914</td></tr></table>	T39 $\frac{1}{2}$ N S32	R21E S33	S5 T39N	S4 R21E	1914	
T39 $\frac{1}{2}$ N S32	R21E S33						
S5 T39N	S4 R21E						
1914							
	N. 0° 03' W. on true line bet. secs. 32 and 33. Over broken land.						
15.00	Begin asc. S. slope.						
35.00	Top of spur, 110 ft. above sec. cor., projects E.; desc. NE. slope gradually 150 ft. to sec. cor.						
40.00	Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.; <table><tr><td colspan="2">$\frac{1}{4}$</td></tr><tr><td>S32</td><td>S33</td></tr><tr><td colspan="2">1917</td></tr></table>	$\frac{1}{4}$		S32	S33	1917	
$\frac{1}{4}$							
S32	S33						
1917							