

Survey of the Subdivisions of T. 39 $\frac{1}{2}$ N., R. 21 E.

Chains

N. 89° 54' W. on true line bet. secs. 20 and 29.
Over broken land.

6.50 Top of spur, projects S. 30° W.; desc. W. slope.

27.40 Ravine, 20 lks. wide, 230 ft. below spur, course N.; asc. very gradual over gently rolling hills.

39.92 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.;

S 20
<hr style="width: 50%; margin: 0 auto;"/>
S 29
1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

79.84 The cor. of secs. 19, 20, 29 and 30.

Land, rolling mountainous, general drainage NE.

Soil, rocky heavy clay loam, good depth, covered with fine coating of sand and gravel.

Scant growth of sage and bunchgrass.

No timber.

N. 89° 56' W. on random line bet. secs. 19 and 30.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.13 Intersect the W. bdy. at a point 9 lks. N. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, 3 ft. long, 3 ins. dia., showing 12 ins. above ground, marked and witnessed as described by the surveyor general. I change the marks on the brass cap to read as follows:

T39 $\frac{1}{2}$ N	
R20E	R21E
S24	S19
<hr style="width: 50%; margin: 0 auto;"/>	
S25	S30
1914	

Thence,

East on true line bet. secs. 19 and 30.

Over rolling land.

14.10 Draw, 20 ft. below sec. cor., course N. 30° W.; asc. NW. slope.