

Survey of the Subdivisions of T. 40 N., R. 21 E.

Chains 16.90	Road, bears N. 30° E. and S. 30° W.
39.98	Set an iron post, 3 ft. long, 1 in. dia., 16 ins. in the ground to solid rock, with mound of stone around, for $\frac{1}{4}$ sec. cor., with brass cap marked;
	$\frac{1}{4}$ S11 S12 1917
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
46.00	Ravine, course N. 70° E.
79.96	The cor. of secs. 1, 2, 11 and 12. Land, rolling, general drainage NE. Soil, rocky heavy clay loam, very shallow, with loose basalt rocks on surface. Scant growth of sage and bunch grass. No timber.
	N. 0° 01' W. on true line bet. secs. 1 and 2. Over broken land.
25.00	Asc. S. slope, bears NE. and W.
34.90	Top of ascent, 30 ft. above bottom of ascent, desc. N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked;
	$\frac{1}{4}$ S 2 S 1 1917
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
43.90	Ravine, 60 ft. below top of ascent, course E.; asc. gradual SE. slope 80 ft. to
89.89	Intersect the 8th St. Par. N., at a point 36.12 chs. N. 88° 56' E. of the S. C. of secs. 35 and 36, at which point set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for C. C. of secs. 1, and 2, with