

Survey of the Subdivisions of T. 40 N., R. 21 E.

Chains
 63.00 Top of ascent, 80 ft. above canyon; desc. over broken rim rock, bears N. 85° W. and S. 85° E.
 74.80 Bottom of canyon, 50 ft. below rimrock, course S. 35° W; ass. S. slope 80 ft. to
 84.96 Intersect the 8th St. Par. N., at a point 31.19 chs.; N. 88° 56' E. of the S. C. of secs. 32 and 33, at which point set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in the ground to solid rock, with mound of stone around, for C. C. of secs. 4 and 5, with brass cap marked;

T41N R21E
 S 33

S 5	S 4
T40N	R21E
C	C
1917	

and raise a mound of stone, 2 ft. base, 1½ ft. high,

S. of cor.

Land, rough mountainous, general drainage to W.
 Soil, rocky and stoney heavy clay loam, 4th rate, exposed ledges of volcanic rock.
 Scant growth of sage and bunch grass.
 No timber.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy.; for description see notes of T. 39½ N., R. 21 E., N. 0° 04' W. on true line bet. secs. 31 and 32.

Over nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ sec. cor., with brass cap marked;

¼
 S31 | S32
 1917

dig pits, 18 X 18 X 12 ins., N. and S. of cor., 3 ft. dist. A series of springs and marshes bears W., 15.00 to 21.00 chs.

60.00 Leave gentle N. slope. Over flat.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the