

Fractional E. bdy. T 28 N, R 23 E.

Chains	
	Desc. rolling S. slope.
69.57	85 ft. below $\frac{1}{4}$ sec. cor. The edge of Winnemucca lake. Set a granite stone, 70 x 20 x 8 ins. , 20 ins. in the ground for meander cor. of fractional secs. 7 and 12 mkd. T 28 N on N. face. R 23 E on W. face, R 24 E on E. face. M C on top, with 6 grooves on the E, and W. faces , and 2 grooves on N. face. Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor. Land, rolling with a slope to the S. Soil, dry and sandy desert loam, 1st. rate, but too dry for successful cultivation. Poor feed of sagebrush, with some grass and other feed. No timber.
	Fractional S. bdy. , T 28 N, R 23 E. Begin at the closing corner of fractional secs..4 and 33, on the Pyramid Lake Indian Reservation bdy. ,previously described in Book B., this cor. is 19.53 chs. east of the cor. of secs. 32 and 33. Thence E. on a blank line, on the S. bdy. of T 28 N, R 23 E., south of sec. 33.
20.47	Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. for sec.s 33, with brass cap mkd. $\frac{1}{4}$ S 33 1916
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.
25.62	The $\frac{1}{4}$ sec. cor. for sec. 4, previously described in Book B.
60.47	Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground for cor. of secs. 33 and 34, with brass cap mkd.