

Independent Resurvey of the S. Bdy. T. 40 N., R. 23 E.

Chains the ground to bed rock and 2 ins. in a mound of stone, for cor. of secs. 31 and 32, with brass cap mkd.

T40N	R23E
S31	S32
T39N	
1919	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Land, nearly level table land. Soil, light, sandy clay loam, medium texture, dry, mixed with gravel and rocks. Undergrowth, sagebrush and a fair growth of grass. No timber.

West, on a true line, on S. Bdy. of sec. 31.

Asc. E. slope of ridge, through undergrowth and over surface covered with loose boulders.

1.03 Intersect the reestablished cor. of secs. 31 and 32, which is an iron post, 3 ins. diam., 10 ins. above the ground, mkd. and witnessed as described by the surveyor general.

I now obliterate all evidence of this cor.

Thence continue with line and measurement.

8.30 Base of cliffs, facing E.; 145 ft. above sec. cor.; bears N. 15° W. and S. 15° E.

9.60 Top of cliff, 50 ft. high, bears N. 15° W. and S. 15° E.; thence asc. over series of ledges.

12.76 Intersect the closing cor. of secs. 5 and 6, T. 39 N., R. 23 E., which is an iron post, 2 ins. diam., firmly set in a mound of stone, mkd. and witnessed as described by the surveyor general. I now obliterate the markings and remark the brass cap as follows:

T40N	R23E
S31	
S6	S5
T39N	R23E
C C	
1919	

Thence continue with line and measurement.

23.40 Top of ascent, 110 ft. above cliff, bears N. and S.; thence over nearly level table land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock and 6 ins. in a mound of stone,