

## Independent Resurvey of the S.Bdy. of T. 40 N., R. 23 E.

- Chains for  $\frac{1}{4}$  cor. of sec. 31, with brass cap mkd.
- $\frac{1}{4}$  S31  
1919
- and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.
- 41.05 Intersect the reestablished  $\frac{1}{4}$  cor. of sec. 31, which is an iron post, 1 in. diam., 16 ins. in a mound of stone, mkd. and witnessed as described by the surveyor general. I now obliterate all evidence of this cor.
- 52.00 Leave nearly level table land and descend abruptly over series of cliffs 75 ft. high, facing W., bears N. and S.
- 61.00 Ravine, 70 ft. below base of cliff, course NW.; asc.
- 77.48 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of Tps. 40 N., Rs. 22 $\frac{1}{2}$  and 23 E., with brass cap mkd.
- T40N  
R22 $\frac{1}{2}$ E | R23E  
S36 | S31  
-----  
T39N  
1919
- and raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
- Land, rough mountainous table land, with many cliffs and sand stone ledges and outcrops, Soil, light, sandy loam, medium texture, dry and rocky. Undergrowth, sagebrush and a fair growth of grass. No timber.

## Independent Resurvey of the E. Bdy. of T. 40 N., R. 23 E.

- From the cor. of Tps. 39 and 40 N., Rs. 23 and 24 E., heretofore described.
- North, on a true line, on E. Bdy. of sec. 36.
- Descend along NE. slope, through scattering sagebrush and over surface covered with loose rocks.
- 5.30 Ravine, drains SE.; asc. SW. slope.
- 26.50 Point of spur, 90 ft. above ravine, falls SE.; desc. N. slope.
- 19.10 Ravine, 65 ft. below spur, drains E.; asc. S. slope.
- 29.00 Point of spur, 100 ft. above ravine, falls SE.; desc. NE. slope.