

## Independent Resurvey of the W. Bdy. of T. 40 N., R. 23 E.

Chains W. of cor.

43.70 Leave rolling land, enter mountainous land, asc. along steep W. slope covered with slide rock, bears N. 20° W. and S. 20° E.

72.00 Point of spur, 245 ft. above base of ascent, projects W.; descend.

76.00 Ravine, 50 ft. below point of spur, course W.; asc.

83.25 Point of spur, 85 ft. above ravine, projects W.; desc.

91.30 Ravine, 200 ft. below point of spur, course W.; asc. 250 ft. to

103.51 Intersect the Eighth Standard Parallel North; at a point 11.25 chs. N. 86° 38' E.; of the true point for standard cor. to secs. 31 and 32, heretofore described. At the point of intersection,  
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for closing cor., to secs. 1 and 6, with brass cap mkd.

S1	S6
R22½E	R23E
T40N	
C C	
1919	

and raise a mound of stone, 3 ft. base, 3 ft. high, S. of cor.

Land, rolling and mountainous. Soil, in bottom land, light loose sandy loam medium texture. The slopes of the mountainous land are covered with sliderock and boulders and many sandstone outcrops and small ledges. Very shallow soil. Undergrowth sagebrush and a fair growth of grass. No timber.

## Independent Resurvey of Subdivisions of T. 40 N., R. 23 E.

From cor. to secs. 25 and 36, on E. Bdy. of Tp., previously described.

West, on a sectional correction line, bet. secs. 25 and 36.

Over rough broken mountainous land; through sagebrush and surface covered with loose rocks; desc. W. slope.