

53⁴

Independent Resurvey of Subdivisions of T.40N., R. 23 E.

- Chains N. 0° 01'W., bet. secs. 1 and 2.
 Over rolling mountainous land, through dense undergrowth.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bed rock and 20 ins. in a mound of stone, for $\frac{1}{2}$ sec. cor., with brass cap mkd.
- S2 | S1
1919
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- 48.50 Precipitous descent of 30 ft. bears NW. and SE.; thence desc. 85 ft. to
- 57.75 Ravine, course NW.; asc.
- 63.20 Point of spur, 25 ft. above ravine, projects W.; desc.
- 71.05 Same ravine, 55 ft. below point of spur, course N.10°E.
- 73.10 Same ravine, course N.30°W.; thence asc. abruptly over broken lava and sandstone cliff.
- 76.90 Top of rimrock, 150 ft. above ravine, bears N.60°W. and S.60°E.; thence asc. SW. slope.
- 85.70 Top of high ridge, 30 ft. above rimrock, bears N.30°W. and S. 30°E.; desc.
- 106.00 Head of gulch, 150 ft. below top of ridge, course S.80°E.; asc. 60 ft. to
- 108.31 Intersect the Eighth Standard Parallel North, 1.73 chs. S.89°22'W. of the Standard cor. of Tps. 41 N., Rs. 23 and 24 E., heretofore described. At the point of intersection.
- Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bed rock and 4 ins. in a mound of stone, for closing cor. of secs. 1 and 2, with brass cap mkd.

S2	S1
T40N	R23E
C	C
1919	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high; S. of cor.

Rolling mountainous table land, covered with lava rocks and many sandstone outcrops. Soil, light sandy shallow