

## Independent Resurvey of Subdivisions of T. 40 N., R. 23 E.

Chains	ground to bed rock and 20 ins. in a mound of stone, for $\frac{1}{2}$ sec. cor., with brass cap mkd.
	$\frac{1}{2}$ S3   S2 1919
	and raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
44.30	Edge of rimrock, bears N. $30^{\circ}$ W. and S. $30^{\circ}$ E.; precipitous descent of 50 ft.; thence desc. 150 ft. to
94.00	Edge of rimrock, bears N. $60^{\circ}$ W. and S. $60^{\circ}$ E.; precipitous descent of 30 ft.; thence desc. 45 ft. to
97.00	Ravine, course N. $20^{\circ}$ W.; asc. 30 ft. to
99.00	Base of cliff, bears N. $5^{\circ}$ W. and S. $5^{\circ}$ E.; ascenl 20 ft. to top.
99.50	Top of cliff; thence over level table land.
107.51	Intersect the Eighth Standard Parallel North, 68 lks. N. $89^{\circ} 22' E.$ , of the standard cor. of secs. 35 and 36, T. 41 N., R. 23 E., previously described. At the point of intersection Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap mkd.
	S3   S2 T40N   R23E C   C 1919
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.
	Rolling mountainous table land. Soil, light sandy shallow clay loam, medium texture, dry and rocky. Undergrowth, sagebrush and a fair growth of grass. No timber.
	From the cor. of secs. 33 and 34, on the S.Bdy. of the Tp., heretofore described.
	N. $0^{\circ} 02' W.$ , bet. secs. 33 and 34.
	Asc. over rolling mountainous table land, covered with loose boulders, through dense undergrowth.
15.00	Point of spur, 75 ft. above sec. cor., projects W.; desc.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{2}$ sec. cor., with brass cap mkd.