

Independent Resurvey of Subdivisions of T. 40 N., R. 23 E.

Chains ascent of 20 ft. to top.  
 68.00 Top of rimrock; thence over rocky level table land.  
 76.65 Edge of table land, bears N.20°E. and S.20°W.; thence desc. 25 ft. over rocky W. slope to  
 79.98 The cor. of secs. 3, 4, 9 and 10.  
 Land, rolling mountainous table land. Soil, light shallow sandy loam, medium texture dry and rocky. Undergrowth, sagebrush and a fair growth of grass. No timber.

N. 0° 02' W., bet. secs. 3 and 4.


Desc. over rocky W. slope, through dense undergrowth.

20.80 Ravine, 185 ft. below sec. cor., course N.70°W.; asc.

30.20 Point of spur, 115 ft. above ravine, projects W.; desc. 65 ft. to

34.50 Gulch, course W.; asc. 50 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor. This cor. is situated on top of point of spur, projects W.; desc. 95 ft. to

44.80 Ravine, course S. 70° W.; asc. 175 ft. over rocky S. slope to

58.00 Top of rimrock, bears N.70°W. and N.70°E.; thence over rolling rocky table land.

93.00 Top of ridge, bears NW. and SE.; desc. gradually, 25 ft. to

106.28 Intersect the Eighth Standard Parallel North, 2.98 chs. N. 89° 22'E. of the standard cor. of secs. 34 and 35, T. 41 N., R. 23 E., heretofore described. At the point of intersection,

Set an iron post, 3 ft., long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd.

