

Independent Resurvey of Subdivisions of T. 40 N., R. 23 E.

- Chains Precipitous descent of 50 ft., bears NE. and SW.; thence
 37.00 desc. abruptly 135 ft. over rocky NW. slope to
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \text{S5} \\ | \\ \text{1919} \\ | \\ \text{S4} \end{array}$$

 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
 of cor.
 45.90 Ravine, 220 ft. below $\frac{1}{4}$ sec. cor., course S. 70° W.;
 asc. abruptly 400 ft. over rocky SW. slope to
 66.00 Base of rimrock, bears N. 30° W. and S. 30° E.; precipitous
 ascent of 45 ft. to top.
 66.80 Top of rimrock, thence asc. 115 ft. to
 77.75 Edge of table land, bears N. 30° W. and S. 30° E.; thence
 over rolling table land.
 105.53 Intersect the Eighth Standard Parallel North, 5.51 chs.
 N. $89^\circ 22' E.$ of the standard cor. of secs. 33 and 34,
 T. 41 N., R. 23 E., heretofore described. At the point
 of intersection,
 Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in
 the ground, to bed rock and 9 ins. in a mound of stone,
 for closing cor. of secs. 4 and 5, with brass cap mkd.

$$\begin{array}{c} \text{S5} \quad \text{S4} \\ \text{T40N} \quad \text{R23E} \\ | \quad | \\ \text{C} \quad \text{C} \\ | \\ \text{1919} \end{array}$$

 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
 S. of cor.
 Land, rough mountainous. Soil, light loose sandy shallow
 loam, medium texture, dry and rocky. Undergrowth, sage-
 brush and a fair growth of grass. No timber.
 From the cor. of secs. 31 and 32, on the S. Bdy. of the
 Tp., heretofore described.
 N. $0^\circ 04' W.$, bet. secs. 31 and 32.
 Desc. over NE. slope, covered with loose boulders, through
 dense undergrowth.