

Independent Resurvey of Subdivisions of T. 40 N., R. 23 E.

Chains	
23.00	Base of cliffs bear N. 30°W. and S.30°E. precipitous ascent of 45 ft. to top.
23.25	Top of cliff; thence asc. abruptly 110 ft. to
27.00	Base of cliff, bears NE. and SW.; thence asc. gradually over rolling table land, 20 ft. to
36.93	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. S6 $\frac{1}{4}$ S7 1919
	and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. Thence asc. 320 ft. to
66.90	Top of ridge, bears N. and S.; thence over nearly level top.
76.93	The cor. of secs. 5, 6, 7 and 8. Land, rough mountainous. Soil, light sandy clay shallow loam, medium texture, dry and rocky. Undergrowth, sage-brush and a fair growth of grass. No timber.
	N. 0° 04'W., bet. secs. 5 and 6. Over rolling table land, through dense undergrowth, and over rocky surface, asc. gradually 20 ft. to
15.00	Top of ascent, bears N.30°W. and S.30°E.; desc. 45 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. S6 $\frac{1}{4}$ S5 1919
	and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. From this cor. the old $\frac{1}{4}$ cor. for secs. 4 and 5 bears N. 37° 17' W. 29.24 chs. Old cor. for secs. 4, 5, 8 and 9 bears S. 43° 01'W. 24.97 chs. Thence desc. 25 ft. to
42.10	Head of ravine, course NE.; asc. 20 ft. to
54.20	Top of spur, projects NE.; desc. 50 ft. to
60.60	Head of ravine, course NE.; asc. 50 ft. to
67.60	Top of spur, projects N.10°E.; thence desc. 255 ft. to
104.65	Intersect the Eighth Standard Parallel North, at a point