

Retracement and Resurvey of the
Second Standard Parallel South through Range 62 E.

chains 33, I retrace East, on the Second Standard Parallel South and S. bdy. of sec. 33.

40.64 Fall 1.12 chs. S. of the standard $\frac{1}{4}$ sec. cor., which is a trachyte stone, 24x10x10 ins., firmly set, 6 ins. in the ground, marked and witnessed as described by the surveyor general.

This falling answers to a true course of N. 89° 36' E. and a distance of 160.64 chs. for the two miles between the std. $\frac{1}{4}$ cor. for sec. 31 and the std. $\frac{1}{4}$ cor. for sec. 33.

I return to the std. cor. of T. 8 S., Rs. 61 and 62 E., heretofore described, and reestablish same in its exact position as follows:

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground for std. cor. of T. 8 S., Rs. 61 and 62 E., with brass cap marked

SC	
T8S	
R61E	R62E
S36	S31

1916

and raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor.

I bury the old std. Tp. cor. alongside of iron post.

From this newly established std. cor. of Tps. 8 S., Rs. 61 and 62 E., just described, I resurvey N. 89° 38' E., on the Second Standard Parallel South and S. bdy. of sec. 31.

Over rolling hilly land, through scattering undergrowth of shadscale, greasewood, ironwood and grass.

16.80 Dry wash, 30 lks. wide, 1½ ft. deep, drains N. 60° E.

39.94 Intersect the std. $\frac{1}{4}$ sec. cor., which I reestablish in exact position as follows:

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins., in the ground for std. $\frac{1}{4}$ sec. cor., with brass cap marked