

Resurvey of the South Boundary of T. 9 S., R 62 E.

chains

E., marked with 5 grooves on E. and 1 groove on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Cor. stands on SW. slope of small spur, 50 ft. below top at 77.10

Land, rough mountainous. Soil; no soil material finer than coarse gravel, much volcanic rock outcrop. No timber. Very little undergrowth or grass.

From the cor. of secs. 31 and 32, S. $87^{\circ} 58'$ W. on a true line along the south boundary of sec. 31.

Over mountainous land. Descend.

3.55 A point by proportionate measurement for the restored cor. of secs. 5 and 6, T. 10 S., R. 62 E.

Set a porphyry stone 18x10x6 ins., 12 ins. in the ground, for cor. of secs. 5 and 6, T. 10 S., R. 62

E., marked with 5 grooves on E. and 1 groove on west face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

11.90 Dry wash, drains S. Ascend.

18.70 Top of spur, 120 ft. above wash, projects S. Descend.

26.10 Top of spur, 30 ft. below top of spur at 18.70.

Descend steep W. slope.

31.20 Gulch, 130 ft. below top of spur, drains SW. Ascend.

40.03 Westing of 40.00 chs.

Set a porphyry stone, 18x12x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 31, marked with $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

43.00 Top of spur, 150 ft. above gulch, projects SW. Descend.

44.66 A point by proportionate measurement for the restored $\frac{1}{4}$ cor. of sec. 6.

Set an iron post, 3 ft. long, 1 in. in dia., on bedrock surrounded by a mound of stone, for $\frac{1}{4}$ cor. of sec. 6 with brass cap marked