Chains

brass cap marked

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Cor stands 20 ft. above gulch.

Land, rolling hills. Soil; very rocky, gravelly, sandy loam. No timber. Undergrowth; greasewood, rabbit brush, yucca, Joshua. Very little grass.

From the cor. of secs. 1, 6, 7, and 12
North, bet. secs. 1 and 6.

Over rolling hills, general drainage to W. and SW. Ascend gradually.

7.60 Dry wash, drains SW.

27.10 Dry wash, drains SW.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground to solid rock, surrounded by a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c|c} \frac{1}{4} \\ s & 1 \\ \hline \\ 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. high, W. of cor. Cor. stands 60 ft. above sec. cor.

44.50 Dry wash, drains S. 80° W. Ascend.

73.00 Top of ridge, 140 ft. above wash, bears NE. and SW. Descend.

81.17 Intersect Second Standard Parallel South and S. bdy. of sec. 36, T. 8 S., R. 62 E, 7.54 chs. W. of S.C. of T. 8 S., R. 62 E.only. heretofore described,

Set an iron post, 3 ft. long, 3 ins. in dia., 16 ins. in the ground to solid rock, surrounded by a mound of stone, for closing cor of Ts 9 S., Rs. 62 and 63 E., with brass cap marked