

## East Boundary of T. 9 S., R. 62 E.

Chains

T 8 S R 62 E
S 36
S 1 S 6
R 62 E R 63 E
T 9 S
C C
1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
S. of cor. Cor. stands 100 ft. below top of ridge.

Land, rolling hills and mountainous. Soil; very rocky,  
sandy loam. No timber. Undergrowth; greasewood,  
rabbit brush, yucca, Joshua. Very little grass.

-----

Subdivision of T. 9 S., R. 62 E.

From the cor. of secs. 25, 30, 31, and 36, on E. bdy. of  
Tp.

West, on a sectional correction line bet. secs. 25 and  
36.

Over gently rolling land, general slope and drainage  
to W. and SW.

17.50 Dry wash, drains S.  $60^\circ$  W.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 20 ins. in  
the ground to solid rock, surrounded by a mound of  
stone, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S 25
$\frac{1}{4}$ -----
S 36

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
N. of cor. Cor. stands 50 ft. below sec. cor.

78.00 Dry wash, drains S.  $70^\circ$  W.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in  
the ground, for cor. of secs. 25, 26, 35, and 36, with  
brass cap marked

T 9 S R 62 E
S 26 S 25
S 35 S 36

1917