

## Subdivision of T. 9 S., R. 62 E.

Chains	$\frac{1}{4}$ sec. cor., and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Impracticable to build mound N. of cor.
48.00	Foot of descent, 400 ft. below top of ridge, bears N. and S. Ascend.
54.80	Top of spur, 150 ft. above foot of descent, projects S. 5° W. Descend.
66.60	Gulch, 370 ft. below top of spur, drains S. 25° W. Ascend.
72.50	Top of small spur, 70 ft. above gulch, projects S. Descend.
78.40	Dry wash, 70 ft. below top of spur, drains S. Ascend.
83.81	Intersect W. bdy. of Tp. 4.24 chs. N. of cor. of secs. 25 and 36, T. 9 S., R 61 E., heretofore described. At point of intersection Set a granite stone, 20x14x6 ins., on bedrock, surrounded by a mound of stone for closing cor. of secs. 30 and 31, marked with 1 groove on S., 5 grooves on N., and C C on E. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor. Cor. stands 130 ft. above wash. Land, very rough mountainous. Soil; very rocky, shallow, coarse sand and gravel; much rock outcropping. No timber. Undergrowth; scattering greasewood, rabbit brush, yucca, Joshua. Very little grass. ----- From the closing cor. of secs. 30 and 31, South, on a true line along the W. bdy. of sec. 31.
4.24	The cor. of secs. 25 and 36, T. 9 S., R 61 E., heretofore described.
40.00	Set a granite stone, 16x12x4 ins., on bedrock, surrounded by a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 31 only, marked $\frac{1}{4}$ on E. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor. -----