	Subdivision of T. 9 S., R. 02 h.
Chains 68.30	Top of spur, 180 ft. above gulch, projects SW. Descend.
77.40	Gulch, 190 ft. below top of spur, drains S. 40° W.
	Ascend.
79.90	The cor. of secs. 1, 2, 11, and 12, 50 ft. above gulch.
- pagid	Land, rolling hills and mountainous. Soil; shallow,
e do Li	very rocky, sandy loam; much rock outcropping. No
y br	timber. Undergrowth; scattering greasewood, rabbit
errorth:	brush, yucca, Joshua. Very little grass.
gards.	o s <u>deponde Linurge ut biddur. Linga mende in in tiret department</u>
	N. 0° 1'W., bet. secs. 1 and 2.
	Over mountainous land. Ascend along E. slope of ridge.
32.30	Top of ridge, 230 ft. above cor., bears N. 80° E. and
	S. 10° W. Descend.
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 16 ins. in
the	the ground to solid rock, in a mound of stone, for $\frac{1}{4}$
	one of carra to some the mount of booms, for 4.
	sec. cor., with brass cap marked
	sec. cor., with brass cap marked $\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	sec. cor., with brass cap marked
	sec. cor., with brass cap marked $\begin{array}{c ccccccccccccccccccccccccccccccccccc$
bi o	sec. cor., with brass cap marked $\frac{\frac{1}{4}}{52} $ S 2 S 1
bi o	sec. cor., with brass cap marked $\frac{\frac{1}{4}}{52} \le 1$ 1917 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
b. o.	sec. cor., with brass cap marked $\frac{\frac{1}{4}}{52} \le 1$ 1917 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
b. o.	sec. cor., with brass cap marked $\begin{array}{c ccccccccccccccccccccccccccccccccccc$
43.90 64.00 79.60	sec. cor., with brass cap marked \[\frac{1}{4} \] \[\sigma 2 \sigma 1 \] \[\sigma 1917 \] and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, \[\text{W. of cor.} \] Gulch, 190 ft. below top of ridge drains W. Ascend \[\text{abruptly.} \] Top of spur, 300 ft. above gulch, projects SW. Descend. Head of gulch, 160 ft. below top of spur, drains S. 30°
43.90 64.00 79.60	sec. cor., with brass cap marked \[\frac{1}{4} \] \[\sigma 2 \sigma 1 \sigm
43.90 64.00 79.60	sec. cor., with brass cap marked \[\frac{1}{4} \] \[\text{S 2} \sigma 1 \] \[\text{1917} \] and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, \[\text{W. of cor.} \] Gulch, 190 ft. below top of ridge drains W. Ascend \[\text{abruptly.} \] Top of spur, 300 ft. above gulch, projects SW. Descend. Head of gulch, 160 ft. below top of spur, drains S. 30° \[\text{W. Ascend.} \]
43.90 64.00 79.60	sec. cor., with brass cap marked 1/4 S 2 S 1 1917 and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Gulch, 190 ft. below top of ridge drains W. Ascend abruptly. Top of spur, 300 ft. above gulch, projects SW. Descend. Head of gulch, 160 ft. below top of spur, drains S. 30° W. Ascend. Intersect Second Standard Parallel South and S. bdy. of sec. 35, T. 8 S., R. 62 E., 7.47 chs. W. of S.C. of
43.90 64.00 79.60	sec. cor., with brass cap marked \[\frac{1}{4} \] \[\text{S 2} \sigma 1 \] \[\text{1917} \] and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high, \] \[\text{W. of cor.} \] Gulch, 190 ft. below top of ridge drains W. Ascend \[\text{abruptly.} \] Top of spur, 300 ft. above gulch, projects SW. Descend. \[\text{Head of gulch, 160 ft. below top of spur, drains S. 30^\circ \] \[\text{W. Ascend.} \] Intersect Second Standard Parallel South and S. bdy. of
43.90 64.00 79.60	sec. cor., with brass cap marked 1/4 S 2 S 1 1917 and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Gulch, 190 ft. below top of ridge drains W. Ascend abruptly. Top of spur, 300 ft. above gulch, projects SW. Descend. Head of gulch, 160 ft. below top of spur, drains S. 30° W. Ascend. Intersect Second Standard Parallel South and S. bdy. of sec. 35, T. 8 S., R. 62 E., 7.47 chs. W. of S.C. of
43.90 64.00 79.60 81.03	sec. cor., with brass cap marked \$\frac{1}{4}\$ \$\$ 2 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
43.90 64.00 79.60 81.03	sec. cor., with brass cap marked 1