

Subdivision of T. 9 S., R. 62 E.

Chains

- 29.00 Leave lake bed and ascend over cliff, bears N. 80° W.
and S. 75° E.
- 31.76 Flag at triangulation point on top of cliff, 250 ft.
high.
- 32.30 Top of ridge, 270 ft. above lake bed, bears N. 80° W.
and S. 75° E. Descend.
- 40.00 Set an iron post, 3 ft. long, 1 in. in dia., on bedrock,
in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap
marked

$\frac{1}{4}$
S 4 | S 3
1917

- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor. Cor. stands 140 ft. below top of ridge.
- 50.30 Gulch, 50 ft. below $\frac{1}{4}$ cor., drains SW.
Enter rolling hilly land, bears E. and W. Ascend.
- 81.27 Intersect Second Standard Parallel South and S. bdy. of
sec. 33, T. 8 S., R. 62 E., 7.55 chs. W. of the S.C.
of secs. 33 and 34.
Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins in
the ground for closing cor. of secs. 3 and 4, with
brass cap marked

T 8 S R 62 E
S 33

S 4 | S 3
T 9 S R 62 E
C C
1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft high,
S. of cor. Cor. stands 40 ft. above gulch.

Land, mountainous and rolling hills. Soil; shallow,
rocky, sandy loam; much rock outcrop. No timber. Under-
growth; scattering greasewood, rabbit brush, yucca,
Joshua. Very little grass.

From the cor. of secs. 28, 29, 32, and 33