


Subdivision of T. 9 S., R. 62 E.

Chains
 41.10 Gulch, 80 ft. below top of spur, drains N. 30° W. Ascend.
 52.90 Ridge, 290 ft. above gulch, bears NW. and SE. Descend.
 66.90 Gulch, 160 ft. below ridge, drains S. Ascend.
 73.80 Top of ridge, 120 ft. above gulch, bears N. 10° W. and
 S. 10° W. Descend.
 83.79 Intersect W. bdy. of Tp. 4.35 chs. N. of the cor. of
 secs. 24 and 25, T. 9 S., R. 61 E.
 Set an iron post, 3 ft. long, 2 ins. in dia., 10 ins. in
 the ground to solid rock, in a mound of stone, for
 closing cor. of secs. 19 and 30, with brass cap
 marked



and raise a mound of stone, 2 ft. base, 1½ ft. high,
 E. of cor. Cor. stands 80 ft. below top of ridge.
 Land, mountainous. Soil; shallow, rocky, sandy loam.
 No timber. Undergrowth; scattering greasewood, rabbit
 brush, yucca Joshua. Very little grass.

South, on a true line along W. bdy. of sec. 30.
 4.35 The cor. of secs. 24 and 25.
 40.05½ Set a granite stone, 14x10x6 ins., on bedrock, in a
 mound of stone, for ¼ sec. cor. for sec. 30 only,
 marked with ¼ on E. face, and raise a mound of stone,
 2 ft. base, 1½ ft. high, E. of cor.

Note: Above cor. set at midpoint for the mile.

From the cor. of secs. 19, 20, 29 and 30
 N. 0° 3' W., bet. secs. 19 and 20.
 Over mountainous land. Ascend gradually along W. slope
 of ridge.
 18.80 Top of spur, 30 ft. above cor., projects W. Descend.
 33.10 Gulch, 180 ft. below top of spur, drains NW. Ascend.