

Subdivision of T. 9 S., R. 62 E.

Chains

- 32.90 Top of spur, 90 ft. above gulch, projects N. 20° W.
Descend.
- 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in
the ground to solid rock, in a mound of stone, for $\frac{1}{4}$
sec. cor., with brass cap marked
- $$\frac{1}{4} \frac{S 18}{S 19}$$
 1917
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor. Cor. stands 170 ft. below top of spur.
- 40.70 Gulch, drains N. 30° W., Ascend.
- 47.80 Top of broad spur, 130 ft. above $\frac{1}{4}$ cor., projects N.
Descend.
- 59.50 Dry wash, 170 ft. below top of spur, drains N. 10° E.
Ascend.
- 77.60 Top of ridge, 200 ft. above wash, bears N. 10° E. and S.
Descend abruptly.
- 83.97 Intersect W. bdy. of Tp. 4.09 chs. N. of the cor. of
secs. 13 and 24, T. 9 S., R. 61 E.,
Set a limestone 20x16x6 ins., on bedrock, in a mound of
stone, for closing cor. of secs. 18 and 19, marked
with 3 grooves on S., 3 grooves on N., and C C on E.
face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft.
high, E. of cor. Cor. stands 160 ft. below ridge.
Land, mountainous. Soil; shallow, very rocky, sandy
loam. No timber. Undergrowth; scattering greasewood,
rabbit brush, yucca, Joshua. Fair growth of grass.
-
- South, on a true line along the W. bdy. of sec. 19.
- 4.09 The cor. of secs. 13 and 24.
- 39.87 Midpoint for the mile.
Set an iron post, 3 ft. long, 1 in. in dia., 14 ins. in
the ground to solid rock, in a mound of stone, for $\frac{1}{4}$
sec. cor. for sec. 19 only, with brass cap marked