

Subdivision of T. 9 S., R. 62 E.

Chains

33.20 Dry wash, drains N.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S 7

1/4 S 18

1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

83.89 Intersect W. bdy. of Tp. 4.13 chs. N. of the cor. of secs. 12 and 13, T. 9 S., R. 61 E.

Set a granite stone, 20x14x8 ins., 8 ins. in the ground to solid rock, in a mound of stone, for closing cor. of secs. 7 and 18, marked with 4 grooves on S, 2 grooves on N., and C C on E. face, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E. of cor.

Land, mountainous and rolling. Soil; shallow, rocky, sandy loam. No timber. Undergrowth; greasewood, rabbit brush, yucca, Joshua. Very little grass.

South, on a true line along the W. bdy. of sec. 18.

4.13 The cor. of secs. 12 and 13.

40.02 Midpoint for the mile.

Set a limestone, 18x12x8 ins., 12 ins. in the ground, for 1/4 sec. cor. for sec. 18 only, marked with 1/4 on E. face, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E. of cor.

From the cor. of secs. 7, 8, 17 and 18

N. 0° 3' W., bet. secs. 7 and 8.

Over mountainous land. Along E. slope of ridge.

7.40 Top of NE. end of ridge, bears N. 20° E. and S. 20° W. Descend NW. slope.

15.70 Leave mountainous, enter rolling land, bears NE. and SW. Continue to descend gradually.