

## Subdivision of T. 9 S., R. 62 E.

## Chains

39.94 Set an iron post, 3 ft. long 1 in. in dia., 21 ins. in the ground to solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$$\frac{\frac{1}{4}}{S 5} \\ S 8$$

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. Cor. stands 20 ft. below sec. cor.

52.90 Dry wash, drains N.  $15^{\circ}$  W.  
 59.90 Dry wash, drains NE.  
 72.00 Dry wash, drains NE.  
 79.88 The cor of secs. 5, 6, 7, and 8, 20 ft. above  $\frac{1}{4}$  cor. Land, rolling, general slope and drainage to north. Soil; rocky sandy loam. No timber. Undergrowth; greasewood, rabbit brush, yucca, Joshua. Very little grass.

-----  
 West, on a true line bet. secs. 6 and 7.

Over rolling land, general slope and drainage to NE.

15.00 Dry wash, drains NE.  
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 14 ins. in the ground to solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\frac{\frac{1}{4}}{S 6} \\ S 7$$

1917

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. Cor. stands 100 ft. above sec. cor.

60.20 Dry wash, drains N.  $20^{\circ}$  E.  
 77.50 Old road, bears NE. and S.  $60^{\circ}$  W.  
 83.77 Intersect W. bdy. of Tp. 4.35 chs. N. of cor. of secs. 1 and 12, T. 9 S., R. 61 E.  
 Set a granite stone, 14x8x8 ins., 9 ins. in the ground, for closing cor. of secs. 6 and 7, marked with 5 grooves