

Subdivision of T. 9 S., R. 62 E.

Chains

80.63 Intersect Second Standard Parallel South and S. bdy. of sec. 31, T. 8 S., R. 62 E., 8.63 chs. S. $89^{\circ} 36'$ W. of the S.C. of secs. 31 and 32.

Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap marked

T 8 S R 62 E
S 31
<hr/>
S 6 S 5
T 9 S R 62 E
C C
1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

Land, level and rolling. Soil; level portion, heavy clay loam; rocky sandy loam on rolling land. No timber. Undergrowth; greasewood, rabbit brush, yucca, Joshua. Very little grass on rolling land, good growth of salt grass on level valley.

Note:

An insufficient number of iron posts were available for monumenting the survey of this township and in their place native stone was used as noted in the foregoing field notes.

From the closing cor. of secs. 6 and 7, on W. bdy. of Tp. North, on a true line along the W. bdy. of sec. 6.

35.65 The $\frac{1}{4}$ sec. cor. for sec. 1.

40.00 Set a granite stone, 14x12x8 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor. for sec. 6 only, marked with $\frac{1}{4}$ on E. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.