

Dependent Resurvey of Fourth Standard Parallel South Through Range 55 $\frac{1}{2}$ East. 3

Chains

71.50 Top of spur, 20 ft. above bottom of gulch, projects NE.; descend.

78.00 Bottom of dry wash, 200 lks. wide, 80 ft. below top of spur, course NE.; ascend SE. slope.

80.00 Set an iron post 3 ft. long, 2 ins. diam., on solid surface rock and in a mound of stone, for the standard cor. of secs. 35 and 36, with brass cap mkd.

T16SR55 $\frac{1}{2}$ E

S	C
S35	S36

1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

Land, mountainous, drainage northerly.

Soil, shallow and rocky clay loam, some exposed ledges of limestone.

Undergrowth, sagebrush, greasewood, shadscale and spanish bayonets.

No timber.

From the standard cor. of secs. 35 and 36.

S. 89° 40' W. on a true line on the S. bdy. of sec. 35.

Over mountainous land ascend.

2.80 Top of spur, 50 ft. above standard sec. cor., projects NE.; descend.

5.60 Dry wash, 50 lks. wide, course NE.; over rolling land.

12.00 Gulch, course SE.; ascend steep E. slope.

34.00 Top of ridge, 630 ft. above bottom of gulch, bears N. 20° E. and S. 20° W.; descend.

34.69 Set an iron post 3 ft. long, 1 in. diam., on solid surface rock and in a mound of stone, for the witness cor. of the standard $\frac{1}{4}$ cor. of sec. 35, with brass cap mkd.

S C

S 35

W C

1917