


Chains



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
W. of cor.

Land, level, drainage to SE.

Soil, gravelly, sandy clay loam, good depth, rocky sub-
soil, covered with scattering loose rocks.


Scattering growth of greasewood and rabbit brush.

No timber.

North on true line bet. secs. 1 and 6, on independent
resurvey of same.

Over nearly level land.

- 6.00 Shallow wash, course E.
- 10.00 Ascend abruptly SE. slope.
- 14.30 Shallow wash, 100 lks. wide, course E.
- 19.60 E. edge of spur, projects same.
- 29.50 Top of ridge, 270 ft. above bottom of ascent, bears
SW. and SE.
- 30.50 Descend N. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 3 ins. in the
ground to solid rock, with mound of stone, around, for
 $\frac{1}{4}$ sec. cor., with brass cap marked;



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
W. of cor.

- 41.10 Center of gulch, 210 ft. below ridge, course E.; asc.
- 45.00 Top of ridge, 80 ft. above gulch, bears NE. and SW.;
- desc. abrupt N. slope.
- 54.50 Low pass, 5.00 chs. wide, 170 ft. below top of ridge,
bears NE.; asc. abruptly.