

Dependent Resurvey of Fourth Standard Parallel South Through Range 56 East. 9

Chains

ground for the standard $\frac{1}{4}$ cor. of sec. 35, with brass cap mkd.

S C

$\frac{1}{4}$ S 35

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Ascend steep E. slope of mountain, 920 ft. to the standard cor. of secs. 34 and 35.

58.61 The old standard cor. of Tps. 16 S., Rs. 56 and 57 E., which is a limestone. 16 X 10 X 4 ins., firmly set in a mound of stone, marked with 6 notches on the E., W. and N. edges. I obliterate the marking on this cor. and remark the cor. "AP" on the S. face.

I now change the bearing of my line to N. 88° 42' W.

80.00 Set an iron post 3 ft. long, 2 ins. diam., on solid rock and in a mound of stone, for the standard cor. of secs. 34 and 35, with brass cap mkd.

S	C
T16S	R56E
S34	S35

1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Land, E. $\frac{1}{2}$ mile, rolling valley, W. $\frac{1}{2}$ mile steep E. slope of mountain.

Soil, sandy and gravelly clay loam on E. $\frac{1}{2}$ mile, stony and rocky on W. $\frac{1}{2}$ mile.

Undergrowth, sagebrush, shadscale, greasewood and joshua trees.

No timber.

N. 88° 42' W. on a true line on the S. bdy. of sec. 34.

Over rough mountainous land, ascend SE. slope.

34.25 Top of ridge, 20 ft. above standard sec. cor., bears NE.