

Chains

Land, nearly level valley and mountainous, drainage of E. 70 chs. northerly, drainage W. 10 chs. SE.

Soil, gravelly and stony clay loam on E. 40 chs., rocky clay loam on W. 40 chs.

Undergrowth, sagebrush, shadscale, Spanish bayonet and joshua trees.

No timber.

From the Standard cor. of secs. 31 and 32.

West on a true line on the S. bdy. of sec. 31.

Over rough mountainous land, asc. abruptly E. slope.

12.20 Top of ridge, 340 ft. above standard sec. cor., bears N. and S.; desc. W. slope.

32.06 Dry wash, 20 lks. wide, 2 ft. deep, 350 ft. below top of ridge, course S.; asc. over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., on surface rock, in a mound of stone for the standard $\frac{1}{4}$ cor. of sec. 31, with a brass cap, marked.

$$\begin{array}{r} \text{S. C.} \\ \frac{1}{4} \text{ S } 31 \\ \hline 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

40.47 The old Standard $\frac{1}{4}$ cor. of sec. 33, T. 16 S., R. 56 E., which is a lime stone, 16 X 11 X 7 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face. I obliterate the marking on this cor. and remark "AP" on the S. face. I now change the bearing of line to N. 89° 49' W.

41.36 Top of low spur, 20 ft. above dry wash, projects SE., desc. slightly.

50.00 Asc. 300 ft. along S. slope of ridge, bears E. and W.

80.01 Set an iron post, 3 ft. long, 3 ins. in diam., on surface rock, in a mound of stone for the Standard cor. of Tps. 16 S., Rs. 55 $\frac{1}{2}$ and 56 E., with a brass cap, marked

$$\begin{array}{r} \text{S. C.} \\ \text{T } 16 \text{ S} \\ \text{R } 55\frac{1}{2} \text{ E } \text{ R } 56 \text{ E} \\ \text{S } 36 \text{ S } 31 \\ \hline 1917 \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,