


Chains

Ascend S. slope.

76.50 Top of ridge, 90 ft. above head of canyon, bears E. and W.;
descend N. slope 20 ft. to the sec. cor.


78.63 A point by proportionate measurement for the re-established
 $\frac{1}{4}$ cor. of sec. 7.

Set an iron post 3 ft. long, 1 in. diam., on surface rock
and in a mound of stone, for the $\frac{1}{4}$ cor. of sec. 7, with
brass cap mkd.



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E.
of cor.

80.03 Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the
ground for the cor. of secs. 1 and 12, with brass cap
mkd.



1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of cor.

Land, valley and mountainous, drainage SE.

Soil, sandy loam on S. 40.00 chs., rocky clay loam with
numerous exposed ledges on N. $\frac{1}{2}$ mile.

Undergrowth, sagebrush, shadscale, greasewood.

No timber.

From the cor. of secs. 1 and 12.

N. $2^{\circ} 08'$ W. on a true line on the E. bdy. of sec. 1.

Over rolling land, descend N. slope.

13.50 Cross head of gulch, 240 ft. below top of ridge, course
N. 10° E.; descend gradual slope.

22.10 Enter valley land, bears E. and W.